

3440HD Series Multi-Directional Dome

H.264 8MP 360° Dome Surveillance System



Advanced Optics

- Four independent HD CMOS sensors
- Superior 8MP 360° surveillance imaging
- Adjustable field of views over IP
- Low light Day/Night technology
- Back Light Compensation (BLC)
- Digital Noise Reduction (DNR)
- On-screen display overlays per view

Rugged Construction

- IP66 Ingress Protection
- Temperature range of -20C to 55C
- Three year standard warranty
- Powder coat aluminum alloy construction

Installation and Interoperability

- Remote PTZ positioning per camera
- 2.8x motorized zoom
- 100° pan - 90° tilt adjustment range
- 2.8 - 8mm zoom range
- Single CAT5e Cable Installation
- Four views, one IP address
- Independent and quad image streams
- ONVIF Profile S support
- H.264/MPEG4 Part 10 encoding
- Standard RTSP video streaming
- Web server configuration
- Operation using PoE+ power
- Pendant, wall and pole mounting bracket options

3490HD Series Night Vision Camera

H.264 Dual Channel Night-Vision Camera



Advanced Night Vision Performance

- ASi uncooled micro bolometer technology
- 640 x 512 or 384 x 288, 17um FPA
- Superior thermal sensitivity of <40 mK
- Flexible lens options to suite application and budget requirements
- Long range detection out to 4km

Superior Daytime Imaging

- Visible spectrum daytime color camera available on 3492-2x00 models
- HD 1280 x 720 image quality
- Autofocus, wide view optics
- Supports daytime thermal imaging for improved situational awareness

Rugged Construction

- Wide operating temperature range, -40°C to 75°C, per Nema TS-2 Test Profile figure 2.1
- Durable IP66 ingress protection
- 2 year standard warranty

Installation and Interoperability

- ONVIF Profile S
- H.264 Base/Main/High profiles and MJPEG encoding
- Web server configuration, operation and viewing
- Single CAT5e/CAT6 cable with PoE+
- Wall, pole mounting options

Embedded Video Analytics

- Real-time scene analysis
- User defined regions of interest
- Fence line detection
- Object direction filters
- Learning targets capabilities



youtube.com/CohuHD
linkedin.com/company/CohuHD
twitter.com/CohuHD
facebook.com/CohuHD
CohuHD.com

3430HD Series Fixed Barrel Camera

H.264 2MP 30x Zoom Surveillance System



Advanced Optics

- Superior 1080p image quality
- 30x optical, 16x digital zoom
- Electronic image stabilization
- Image defog/dehaze analytics
- Wide dynamic range
- Backlight compensation
- Flexible exposure adjustments
- 3D noise reduction
- Image rotation adjustments

Rugged Construction

- Built-in electrical transient/surge protection to CISPR 24 levels
- IP68 ingress protection
- Wide operating temperature range
- Faceplate heater blanket

Flexible Installation and Interoperability

- ONVIF Profile S Support
- Power over Ethernet
- H.264 and MJPEG encoding
- Three individually configurable video streams
- Web server configuration, operation and viewing
- Single Cat5e cable installation
- Wall, pole and corner mounting bracket options

The CoHuHD Costar Difference



ADVANCED OPTICS

See farther, with greater detail, thru haze, with less light

INTEROPERABILITY

Open Standards, Non-Proprietary, Seamless Operation




EXPERIENCE

Video Design and Integration Expertise for Over 70 Years, with 1,000's of Satisfied Customers World Wide

RUGGED DESIGN

Reliable and Versatile, Electrical, Mechanical, Environmental Performance



[youtube.com/CohuHD](https://www.youtube.com/CohuHD)
[linkedin.com/company/CohuHD](https://www.linkedin.com/company/CohuHD)
twitter.com/CohuHD
[facebook.com/CohuHD](https://www.facebook.com/CohuHD)
CohuHD.com

©CohuHD Costar™, LLC reserves the right to change specifications without notice